

MAGNUS 728

SOLVENT EMULSION FOAM CLEANER

PRODUCT USE:

MAGNUS 728 is a liquid foaming solvent emulsion cleaner recommended for heavy-duty cleaning of exhaust-track areas of painted or unpainted aircraft surfaces. Can also be used for general aircraft cleaning. It is an excellent grease and oil remover when diluted with water instead of the usual solvents.

ADVANTAGES:

- Certified to meet ASTM F 519 Type 16 Hydrogen and Embrittlement Test.
- Removes exhaust stains without damaging protective clothing.
- Biodegradable.
- Conforms to Boeing Document D6-17487 Class A.
- Conforms to Douglas Document CSD-1 Type II Carbon remover.
- Meets US specification MIL-C-43616 B.

PRODUCT DESCRIPTION:

Appearance:	Slightly blind, yellow liquid
Foam:	Yes
pH:	11.0 -13.0
S.G.:	0.96 - 0.97
Flash Point (Concentrate)	62°C min
Freeze thaw stable:	Yes

DIRECTIONS FOR USE:

General cleaning of painted and unpainted surfaces: Use 1 part **MAGNUS 728** with up to 9 parts of water. Apply with a foam generator and allow dwelling for 5 to 10 minutes. Scrub with mop or brush and rinse thoroughly. **MAGNUS 728** can also be applied by spray, mop or brush. Allow to stand for 3 to 6 minutes, then scrub with a mop or brush. Rinse thoroughly with water.

NOTE: Do not allow the solution to dry on the surface before rinsing, as this will reduce the cleaning efficiency.

Heavy-duty cleaning for heavy deposits and exhaust track areas: Use 1 part **MAGNUS 728** with 4 parts of water.

Wheel-well cleaning: Make a viscous mixture by diluting **MAGNUS 728** 1 : 1 with water.

Ref. No. 01/24

PRECAUTIONS:

- Avoid prolonged breathing of vapour and contact with skin. Wear protective gear.
- Rubber gloves and goggles should at all times be worn when handling the product.
- Store in segregated and approved area.
- Product is flammable.
- Reactive to acids and oxidizing agents.



Product Data Sheet

FIRST AID:

- External: In case of contact with skin or eyes, flush with plenty of cool running water for at least 15 minutes. Get Medical Attention!
- Eyes: Immediately flush eyes with plenty of cool running water for at least 15 minutes. Get Medical Attention.
- Internal: If swallowed, immediately drink a large quantity of water. Get medical attention.

Every endeavour has been made to ensure that the information in this Data Sheet is reliable, but we do not accept any liability for any loss, injury or damage which may result from its use.



Cernol Chemicals (Namibia) (Pty) Ltd
Etienne Rousseau Street, Northern Industrial Area, Windhoek Tel: 061-262 985
E-mail: cernolprocure@swacogroup.com / cernolsales@swacogroup.com / cernolinfo@swacogroup.com
www.swacogroup.com.na

