

MAGNUS 91

ALUMINIUM SAFE LOW FOAMING ALKALINE CLEANER

PRODUCT USE:

MAGNUS 91 is used as a spray washing compound for removing oil, drawing lubricant and dirt from aluminium and its alloys. Highly effective when used in a spray cabinet washer.

ADVANTAGES:

- Low foaming characteristics.
- Suitable for hard and soft water.
- Inhibited against attack on aluminium.
- Keeps spray washers free from lime scale deposits.

PRODUCT DESCRIPTION:

Form: Free flowing off-white powder.

Ingredients: Blend of alkaline salts, inhibitors and low foaming surfactants.

DIRECTIONS FOR USE:

MAGNUS 91 is used at concentrations varying from 5 g/litre to 25 g/litre depending on the nature of the soil to be removed. A temperature of 70 - 80 °Celsius is recommended.

Spray pressures are variable and are dependent on the type of equipment being used.

A water rinse is required after cleaning.

Ref. No. 01/24

PRECAUTIONS:

- Keep out of reach of children.
- Product is mildly alkaline.
- Avoid skin contact. Wear necessary protective gear.
- Do not re-use container.

FIRST AID:

External: In case of contact with skin, flush with plenty of cool running water for at least 15 minutes. Get medical attention if needed.

Eyes: Immediately flush eyes with plenty of cool running water for at least 15 minutes. Get medical attention.

Internal: If swallowed, immediately drink a large quantity of water. Do not induce vomiting. Get medical attention.

Every endeavour has been made to ensure that the information in this Data Sheet is reliable, but we do not accept any liability for any loss, injury or damage which may result from its use.