

OSE 750

LOW TOXICITY OIL-SPILL DISPERSANT

PRODUCT USE:

OSE 750 is used for the dispersing of oil at sea, in harbors, on rocks and beaches.

ADVANTAGES:

- Highly efficient on a variety of oils, from crude to heavy fuel oil.
- Low toxicity.
- Non-corrosive to all common metals and alloys.
- High flash point.
- No fumes when sprayed.

PRODUCT DESCRIPTION:

Appearance:	Pale-yellow liquid
S.G. (at 20 °Celsius):	0.76 - 0.80
Flash Point:	105°Celsius

DIRECTIONS FOR USE:

OSE 750 is sprayed undiluted directly onto the slick or patch of oil. The quantity required will depend on the nature and age of the oil. For example, heavy fuel oil and aged crude requires more than does fresh crude oil. The quantity is varied by the delivery rate of the spray nozzle, the number of nozzles and the speed with which the spray transverses the slick.

The mixture of oil and dispersant must then be thoroughly mixed by means of surface breakers, water jets or, in the tidal zone, by wave action.

EQUIPMENT:

There is very little restriction on equipment. Avoid spray equipment that atomizes the spray. **OSE 750** will tend to swell certain rubbers after prolonged contact. The Warren-Spring designed equipment has been found to be eminently suitable.

Ref. No. 01/24

PRECAUTIONS:

- Keep out of reach of children.
- Product is flammable.
- Wear goggles and gloves when handling the product. Causes skin irritation.
- May be fatal if swallowed.

FIRST AID:

External:	In case of contact with skin or eyes, flush with plenty of cool running water for at least 15 minutes. Get medical attention if needed.
Eyes:	Immediately flush eyes with plenty of cool running water for at least 15 minutes. Get medical attention.
Internal:	If swallowed, immediately drink a large quantity of water. Do not induce vomiting. Get medical attention.

Every endeavor has been made to ensure that the information in this Data Sheet is reliable, but we do not accept any liability for any loss, injury or damage which may result from its use.

