

RLF 4

GENERAL-PURPOSE SYNTHETIC FOAM COMPOUND

PRODUCT USE:

RLF 4 is a general-purpose fire-fighting foam suitable for low, medium and high-expansion equipment.

ADVANTAGES:

- Can be used with salty water, including sea water.
- Long shelf-life.
- Non-corrosive.
- No objectionable odour.
- Inexpensive.

PRODUCT DESCRIPTION:

Appearance: Off-white to yellow liquid
S.G.: 0.98 - 1.00
pH: 6.4 - 7.40

DIRECTIONS FOR USE:

- Use at a 2% - 6 % dilution with water, dependent on conditions of use and type of equipment. (5 litres product per 100 L water).
- Water loss after 5 minutes is 55 % - 65 %
- Water loss after 20 minutes is 75% - 90%,
- Initial water dropout occurs at not less than 2 minutes.
- Water retention after 25 minutes is greater than 20%.
- Expansion ratio: (5L foam / min.) = 1 : 7,0.

Product is not recommended for polar solvent fires, unless application rate of foam far exceeds the defoaming action of the burning solvent.

Ref. No: 01/24

PRECAUTIONS:

- Keep out of reach of children.
- Do not ingest.

FIRST AID:

Eyes: Immediately flush eyes with plenty of cool running water for at least 15 minutes.
Internal: If swallowed, immediately drink a large quantity of water. Do not induce vomiting. Get medical attention.

Every endeavour has been made to ensure that the information in this Data Sheet is reliable, but we do not accept any liability for any loss, injury or damage which may result from its use.