

VECOM B 80 AIRCOOLER CLEANER

FOR MANUAL AND "IN SERVICE" CLEANING OF DIESEL ENGINE charged
with AIR COOLERS

PRODUCT USE:

VECOM B 80 AIRCOOLER CLEANER is light yellow liquid for cleaning Diesel Engine charged with Air coolers.

PRODUCT DESCRIPTION:

Appearance: Light yellow liquid.
S.G.: 0.88 - 0.90

APPLICATION BY:

- Immersion bath.
- Circulation method.
- Direct injection.
- Injection system.

DIRECTIONS FOR USE:

Product should be dosed at the ratio of 2 parts water added to 1 part (in that order) and mixed well for **immediate** use.

If the emulsion is left standing for up to 5 minutes its composition will change and the effectiveness is reduced. It is most important that after 5 - 10 minutes after dosing the solution, the injection with fresh water only is repeated, using double the volume of the first solution to flush off the chemical residual which contains the "dissolved" contamination.

Ref. No. 01/24

PRECAUTIONS:

- Keep out of reach of children. Hazardous.
- Harmful in contact with skin and if swallowed. Wear suitable protective gear.
- Do not breathe the gas/fumes/vapor/spray.
- Keep away from heat.
- Do NOT ingest.
- Avoid all possible sources of ignition (spark of flames).

FIRST AID:

External: In case of contact with skin, flush with plenty of cool running water for at least 15 minutes. Get medical attention if needed.

Eyes: Immediately flush eyes with plenty of cool running water for at least 15 minutes. Get medical attention.

Internal: If swallowed, immediately drink a large quantity of water. Do not induce vomiting. Get medical attention.

Every endeavour has been made to ensure that the information in this Data Sheet is reliable, but we do not accept any liability for any loss, injury or damage which may result from its use.



E-mail: cernolprocure@swacogroup.com / cernolsales@swacogroup.com / cernolinfo@swacogroup.com

Cernol Chemicals (Namibia) (Pty) Ltd

Etienne Rousseau Street, Northern Industrial Area, Windhoek Tel: 061-262 985

www.swacogroup.com.na

